

Aluminum Chainwheels

Used to Operate Overhead Valves from the Floor

SPROCKET-TYPE
using single loop
cut chain

Aluminum Chainwheels allow operation of valves, actuators, or gear boxes in high, hard-to-reach locations by means of a slight pull on the chain. The light weight of aluminum Chainwheels is desirable to minimize the weight on the stems. Universal design allows Chainwheel to be clamped to a handwheel, or pinned directly to the stem.

All Aluminum Chainwheels are A356-T6 alloy and are provided with a protective coating.

Aluminum Chainwheels are furnished with stainless steel attachment hardware for clamping to a handwheel. When Chainwheel is to be pinned to the stem, direct mount adapters are available. The adapters require pinning to the stem as illustrated on page G-62. Adapter is pre-drilled with pin hole, and supplied with a stainless steel pin for customer mounting to the stem. Drilling of the stem by customer.

To prevent serious injury, we recommend the use of our Secondary Safety Restraint System (see pages G-65 and G-66 for more information). All Trumbull Chainwheels are furnished with a threaded boss for the addition of our Safety Restraint System.



Trumbull Item No.	Size No.	Diameter	Boxed Weight	Handwheel OD Range Chainwheel will Fit	Chain Size	Galvanized Chain	Stainless Chain	Chain Length (2X drop) plus...
						Trumbull Item No.	Trumbull Item No.	
367-2020	TRA-0.0	4"	1.05 lbs.	2" to 4"	#2	172-1650	----	1 ft.
367-2021	TRA-1.0	6"	2.65 lbs.	4-1/4" to 5-3/4"	1/0	367-1894	367-1897	1 ft.
367-2022	TRA-1.5	7-1/2"	4.15 lbs.	6" to 7-1/2"	1/0	367-1894	367-1897	1 ft.
367-2023	TRA-2.0	9"	5.30 lbs.	7-3/4" to 9"	1/0	367-1894	367-1897	1-1/2 ft.
367-2024	TRA-2.5	12-1/2"	7.90 lbs.	9-1/4" to 12-1/2"	4/0	367-1895	367-1898	1-1/2 ft.
367-2025	TRA-3.0	15-1/2"	10.40 lbs.	12-3/4" to 15-1/2"	4/0	367-1895	367-1898	2 ft.
367-2026	TRA-3.5	19"	13.30 lbs.	15-3/4" to 19"	4/0	367-1895	367-1898	2-1/2 ft.

When ordering, indicate the Chainwheel and chain size numbers and the number of feet of chain required. Chain is provided in continuous lengths and easily cut in the field to exact length needed. Closing the loop is simple with Connecting Links (shown on right), see page G-63 for more info.

Ductile Iron and Aluminum Chainwheels are sprocket-type, using single loop cut chain. See page G-59 for Chainwheel dimensions.



Connecting Links

Chain Size	Galvanized		316 Stainless	
	Trumbull Item No.	Weight	Trumbull Item No.	Weight
1/0	367-1994	0.02 lbs.	367-1997	0.02 lbs.
4/0	367-1995	0.03 lbs.	367-1998	0.03 lbs.
5/0	367-1996	0.05 lbs.	----	----