


CLAMPING HARDWARE



Attachment Sets



Clamping Disc Hardware

Mounting of Chainwheels

Attachment sets and discs used to mount Chainwheels to handwheel

Each Trumbull Chainwheel is furnished standard with Clamp-On Attachment Hardware. The smaller sizes furnished with Clamping Discs, and larger sizes with Attachment Sets, as outlined below.

Sprocket-Type Chainwheels

- Sizes TR/A-0.0 and TR/A-1.0 use Clamping Disc hardware.
- Sizes TR/A-1.5 to TR/A-2.5 use two sets of Clamp Bases & Arms, plus one Band.
- Sizes TR/A-3.0 to TR/A-5.0 use three sets of Clamp Bases & Arms and do not use a Band.

Pocket-Type Chainwheels

- Sizes TRS/CS-4 & TRS/CS-6 use Clamping Disc hardware.
- Sizes TRS/CS-8 to TRS/CS-29 are furnished standard with size "B" Attachment Sets. Pocket Chainwheels can fit handwheel diameters outside these ranges by using optional Hardware Sets "A" and "C" as shown on chart below.

Pocket Handwheel O.D. Ranges

Size	"A" Attachment Set		"B" Attachment Set		"C" Attachment Set	
	Min. O.D.	Max. O.D.	Min. O.D.	Max. O.D.	Min. O.D.	Max. O.D.
TRS/CS-8	6"	8"	7-1/2"	10-1/2"	12-1/2"	15-1/2"
TRS/CS-12	7"	11"	8-1/2"	13-1/2"	13-1/4"	18-1/2"
TRS/CS-15	8"	15"	9-1/2"	17-1/2"	14-1/8"	23"
TRS/CS-22	11"	22-1/2"	13"	25"	17-1/2"	30"
TRS/CS-29	16"	29"	17-3/4"	32"	22-1/2"	37"