



STAINLESS STEEL CHAINWHEELS

316 STAINLESS STEEL - MODEL TMPTCSS



DESCRIPTION:

Stainless Steel Chainwheels allow operation of valves, actuators, or gear boxes in high, hard-to-reach locations by means of a slight pull on the chain. These are Pocket-Type chainwheels which use specifically calibrated machine chain and connecting links.

These chainwheels are furnished with stainless steel hardware for clamping to a handwheel or can be pinned directly to a stem with optional Star Adapter.

To prevent serious injury, we recommend the use of our Secondary Safety Restraint System.



TRUMBULL CALIBRATED MACHINE CHAIN

Description	Weight
316L SS Machine Chain	0.35 lbs./ft.
SS Connecting Link	0.05 lbs.
Order Length of chain required and connecting link	

STAINLESS STEEL CHAINWHEELS

Size No.	Diameter	Boxed Weight	Handwheel Range Chainwheel will Fit**	Bore*** Diameter	Chain Length (2X Drop)
TRS-4D*	4-1/8"	4.75 lbs.	1-1/2" I.D. to 4-1/2" O.D.	0.500	Plus 1 ft.
TRS-6D*	5-7/8"	8.65 lbs.	2-1/8" I.D. to 6-1/4" O.D.	0.850	Plus 1 ft.
TRS-8B	8"	14.40 lbs.	7-1/2" O.D. to 10-1/2" O.D.	1.500	Plus 1-1/2 ft.
TRS-12B	11-5/8"	19.80 lbs.	8-1/2" O.D. to 13-1/2" O.D.	1.500	Plus 1-1/2 ft.
TRS-15B	15-3/16"	23.90 lbs.	9-1/2" O.D. to 17-1/2" O.D.	1.500	Plus 2 ft.
TRS-22B	22-1/4"	34.45 lbs.	13" O.D. to 25" O.D.	1.500	Plus 3 ft.
TRS-29B	29-1/4"	48.00 lbs.	17-3/4" O.D. to 32" O.D.	1.500	Plus 4 ft.
TRS-29C	29-1/4"	48.00 lbs.	22-1/2" O.D. to 37" O.D.	1.500	Plus 4 ft.

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	