

Main Valve Keys



T-Handle Main Valve Keys

- Handles & shafts fabricated from 1" Sch 40 steel pipe
- Cast steel socket that fits 2" square operating nut
- For more info concerning the Lighted Main Valve Keys, see page A-11.

LIGHTED

Length	Weight	1 Trumbull Item No.	3 Trumbull Item No.
2 ft.	9.15 lbs.	367-5016	spec/ord
3 ft.	10.70 lbs.	367-5017	spec/ord
4 ft.	12.10 lbs.	367-5018	367-5118
5 ft.	13.35 lbs.	367-5019	367-5119
6 ft.	15.30 lbs.	367-5020	367-5120
7 ft.	17.10 lbs.	367-5021	spec/ord
8 ft.	18.80 lbs.	367-5023	367-5123
10 ft.	20.00 lbs.	367-5026	spec/ord
12 ft.	22.00 lbs.	367-5028	spec/ord

Ring Handle Main Valve Keys

- Features a forged steel top ring
- 1" Sch 40 steel pipe shafts
- Cast steel socket fits 2" square operating nut

Length	2 Trumbull Item No.	Weight
4 ft.	367-5124	11.40 lbs.
5 ft.	367-5125	13.00 lbs.
6 ft.	367-5126	14.30 lbs.
7 ft.	367-5127	15.50 lbs.
8 ft.	367-5128	18.00 lbs.



For special lengths not shown here, please inquire.

Telescoping Main Valve Keys

- Adjustable to fit valve depths of 6' through 10'
- 1-1/2" square upper shaft, 1-1/4" square lower shaft
- Steel socket cast with open top mud relief
- Socket fits 2" square operating nut
- Adjustable in one foot increments with wire lock pin

4 Trumbull Item No.	Length	Weight
367-5129	6 ft. through 10 ft.	38.50 lbs.

Gate Valve Speed Wrench

- Allows use of both hands for extra leverage
- Revolving handle allows quick opening & closing

5 Trumbull Item No.	Handle Length	Weight	Ideal for operating valves with 2" AWWA nut in the trench or in the yard.
367-9981	18"	6.20 lbs.	