

Trumbull Manufacturing

3850 Hendricks Road, Youngstown, Ohio 44515

Phone: 330.270.7888 | 877.504.1507 |

Toll Free:

330.392.0756

-www.trumbull-mfg.com

11-1/8" Sealed Floor Boxes

Available in Cast Carbon Steel and Cast Stainless Steel



Trumbull Sealed Floor Boxes are ideal to prevent fluids and vapors from penetrating the floor slab from either direction. Top side is sealed by a Buna-N O-ring, and bottom side can be sealed by use of optional packing gland. Overall length is 11-1/8", but the underside is tapped to accept 2-1/2" NPT steel pipe nipples for floors thicker than 11". When it's necessary to extend a Floor Box for thicker floors, use a 2-1/2" pipe nipple, 1/2" longer than the increase required, as the threads on the underside of the Floor Box are 1/2" deep.



Tapped 2-1/2" threads also permit threading 2-1/2" pipe into underside of Floor Box, to provide an external casing for a smaller internal extension stem.

Floor Boxes

	Material	Item №	Weight
	Cast Carbon Steel*	367-4622	31.05 lbs.
Ī	Cast 316 Stainless Steel	367-4621	33.45 lbs.

^{*} Carbon steel models are EDP coated.

PACKING GLAND

with stainless steel follower seals bottom of Floor Box

BRASS BUSHING

aligns extension stem when bottom seal is not utilized

POSITION INDICATOR

can be used with either brass bushing or packing gland, see Pages F-7 and F-8 for Trumbull Valve Position Indicator installation in floors.



See Page G-13 for other custom options.



